# BOBCAT A300






## Dimensions: 84 2 in (1880 mm) 160.6 in. 128.8 in. (3272 mm 33.9 in. (859 mm) 80.9 in. (2055 mm) 99.1 in. (2517 mm) 48.3 in. 8.5 in. (216 mm 62.2

114.5 in.

142.9 in.

#### A300 AWD Skid Steer Loader



Two different steering modes to match your job!

Go from 4-wheel steer to skid-steer mode at the flip of a switch!

All-Wheel Steer Mode: The Bobcat A300 is a revolutionary compact loader with four steerable axles. That means less tire wear, less ground disturbance.

Skid-Steer Mode: Flip a switch and you get all the advantages of a skid-steer. The A300 maneuvers in tight spaces, turns within its own length, and delivers high performance day-in, day-out.

#### **Specifications**

n	ad	ρı	۲	
~"		ייי		

Rated Operating Capacity (ROC)

Tipping Load

Lift Height to Bucket Pin

Lift Arm Path

### **Size and Speed**

Operating Weight Width (with bucket)

Cab Height

Travel Speed - Low

Travel Speed - High

### **Engine**

Horsepower

Type

**Fuel Tank Capacity** 

**Dual Path Cooling System** 

Engine Shutdown Protection Feature

Bobcat SmartFAN™

Horsepower Management

### **Chaincase**

Chain Size

Axle tubes welded to chaincase Labyrinth Axle Seal Protection

Required Chain Adjustment

#### **Tires**

(1580 mm)

74.0

Bobcat Heavy Duty, 12 ply, 12-16.5 Bobcat Severe Duty, 12 ply, 12-16.5 Bobcat Severe Duty, Poly Filled Bobcat Super Float (33x15.5-16.5)

## A300

3000 lb (1362 kg) 6111 lb (2772 kg)

10' 9" (3.3 m)

Vertical

8673 lb (3934 kg)

74" (1880 mm)

80.9" (2055 mm)

6.9 mph (11.1 km/h)

12.0 mph (19.1 km/h)

#### Tier II Compliant

81

Turbo Diesel

23 gal (87 L)

Std

Std

Std

Std

120 HSOC Std

Std

Never

Std

Opt

Opt Opt

