BOBCAT S185 & S175





Dimensions: 78.8 in. (2001 mm) 152.1 in. (3863 mm) 118.2 in. 29.6 in. (3002 mm) (752 mm) 91.0 in. 76.3 in. (1938 mm) (2310 mm) 7.5 in. (191 mm) 40.6 in. _____ 101.8 in. (2586 mm) 130.3 in.

(3309 mm)

S185 & S175 Skid Steer Loader





Bobcat S175 and S185 loaders are the state-of-the-art work environment that will save you time, effort and money on every job! These are the machines that set the standard for design, productivity and comfort in skid-steer loaders! The impressive rated operating capacity and 118-inch lift height plus vertical lift path and 29.6-inch reach make the S175 and S185 ideal for truck loading

Specifications

Performance

Rated Operating Capacity¹ ROC with Optional Counterweight Tipping Load Hydraulic Pump Capacity High Flow Option Travel Speed Operating Weight

Dimensions

Length (with bucket) Width (with bucket) Height Height to Bucket Pin

Engine

Make/Model Fuel/Cooling Cylinders SAE NET HP/Displacement **Fuel Tank Capacity**

Operation

Steering and Drive

Hydraulics

Transmission

Standard Features

"A" 10 - 16.5 TIRES - 66.0" (1676 mm) or 60.0" (1524 mm) 31.5 x 13 - 16.5 TIRES - 66.0" (1676 mm) 10 - 16.5 TIRES - 54.5" (1385 mm)

31.5 x 13 - 16.5 TIRES - 52.3" (1328 mm) 62 in. BUCKET WIDTH - 62.0" (1575 mm) 68 in. BUCKET WIDTH - 68.0" (1727 mm) 74 in. BUCKET WIDTH - 74.0 (1880 mm)

or 48.5" (1232 mm)

175	_	S 1	
			=
- 1 / 1			u

1750 lb. (794 kg)	1850 lb. (839 kg)
1850 lb. (839 kg)	1950 lb. (885 kg)
3900 lb. (1769 kg)	3900 lb. (1769 kg)
16.9 GPM (63 L/min.)	16.9 GPM (63 L/min.)
26.4 GPM (102 L/min.)	26.4 GPM (102 L/min.)
7.3 MPH (11,3 km/hr.)	7.3 MPH (11.3 km/hr.)
5808 lb. (2635 kg)	5808 lb. (2635 kg)

130.3 in. (3309 mm) 130.3 in. (3309 mm) 68.0 in. (1727 mm) 68.0 in. (1727 mm) 76.3 in. (1938 mm) 76.3 in. (1938 mm) 118.2 in. (3002 mm) 118.2 in. (3002 mm)

Kubota/V2203M-DI Kubota/V2003M-DI-T Diesel/Liquid Diesel/Liquid 56/122 in.3 (2.0 L) 46/134 in.3 (2.2 L) 23 gal. (87.1 L) 23 gal. (87.1 L)

Forward, reverse, travel speed and steering controlled by two hand levers. Raise/lower lift arms and dump/rollback bucket controlled by two foot pedals or optional hand controls. Hydrostatic, four-wheel drive.

Adjustable Cushion Seat Automatically Activated Glow Pluas **Bobcat Interlock Control** System (BICS™) Bob-Tach Deluxe Cab **Dual Path Cooling System** Engine/Hydraulic Shutdown Front Auxiliary Hydraulics Front & Rear Lights

Lift Arm Support Gauges/Warning Lights Operator Cab Parking Brake Seat Bar (available for all Bobcat loaders) Seat Belt Spark Arrestor Muffler (\$175 only 10-16.5 Bobcat Standard **Duty Tires** Turbo-Charger (\$185 only) (Approved Spark Arrestor)



