



S300 Skid Steer Loader

The Truck-Loading Loader!

Designed to deliver more power for more lift, the S300 is the ideal machine for any application requiring strength and lifting ability. Powerful, vertical-path lift arms deliver over 1300kg Operating Capacity. With that kind of muscle, you can easily handle big loads.

Specifications

Performance

	S250	S300
Rated Operating Capacity ¹	2500 lb. (1134 kg)	3000 lb. (1361 kg)
Tipping Load	5000 lb. (2268 kg)	6000 lb. (2722 kg)
Hydraulic Pump Capacity	20.7 GPM (78.4 L/min.)	20.7 GPM (78.4 L/min.)
High Flow Option	30.9 GPM (116.2 L/min.)	30.9 GPM (116.9 L/min.)
Travel Speed	6.9 mph (11.1 km/hr.)	6.9 mph (11.1 km/hr.)
Two-Speed Option	6.9 mph (11.1 km/hr.)	6.9 mph (11.1 km/hr.)
– Low Range	12.0 mph (19.3 km/hr.)	12.0 mph (19.3 km/hr.)
– High Range		
Operating Weight	7723 lb. (3503 kg)	8140 lb. (3692 kg)

Dimensions

Length (with bucket)	142.9 in. (3630 mm)	142.9 in. (3630 mm)
Width (with bucket)	74.0 in. (1880 mm)	74.0 in. (1880 mm)
Height	80.9 in. (2055 mm)	80.9 in. (2055 mm)
Height to Bucket Pin	126.4 in. (3211 mm)	126.4 in. (3211 mm)

Engine

Make/Model	Kubota V3300M-DI-T	Kubota V3300M-DI-T
Fuel/Cooling	Diesel/Liquid	Diesel/Liquid
Cylinders	4	4
HP/Displacement	75.0 hp/202.53 in. ³ (56.9 Kw/3,318 L)	81.0 hp/202.53 in. ³ (60.4 Kw/3,318 L)
Fuel Tank Capacity	25 gal. (94.6 L)	25 gal. (94.6 L)

Tier II Compliant

Operation

Steering and Drive

Forward, reverse, travel speed and steering controlled by two hand levers.

Hydraulics

Raise/lower lift arms and dump/rollback bucket controlled by two foot pedals or optional hand controls.

Transmission

Hydrostatic, four-wheel drive.

Standard Features

Adjustable Cushion Seat	Front & Rear Lights
Automatically-Activated Air Intake Heater	Gauges/Warning Lights
Bobcat Interlock Control System (BICS™)	Lift Arm Support
Bob-Tach™	Operator Cab
Deluxe Cab	Parking Brake
Dual-Path Cooling System	Seat Bar
Engine/Hydraulic Systems Shutdown	Seat Belt
Front Auxiliary Hydraulics	12-16.5 Bobcat Heavy-Duty Tires
	Top & Rear Windows
	Turbo-Charger (approved spark arrestor)

Dimensions:

